



Installation

Please read all installation instructions prior to beginning! The instructions will apply to both our pannier mount kits and the top rack kits. The fundamentals are the same.

If you have any questions about your installation, contact us at support@bullrack.com

When you have your BULLRACKS up on the wall, email us at support@bullrack.com with some pictures of your installation and we will post them on our website!

Your BULLRACK kit comes complete with all the hardware that is normally required to mount the rack(s) in your garage. If you have an unusual situation, you may have to obtain the screws or fasteners you need at your local hardware store.

Each package comes with 2 BULLRACK Wall Racks, or a single top case mount plus screws that are 2 1/2" x #10 for wood mounting.



Wood Stud Installation:

You can install the BULLRACKS anywhere on the stud vertically, so determine where the best location will be for security and ease of access. Typical installations are side by side or over/under. Certain BULLRACK kits (like the BMW K1600 or 1200RT-LC and Yamaha FJR) contain a “left” and a “right” unit. Most garages are

BULLRACK

constructed with 2 x 4 studs and covered with sheetrock. A 2 x 4 is actually only 1 1/2" wide on the side we are screwing into so your target behind the sheet rock is fairly narrow. It is very important that your BULLRACK is attached into the center of the wood stud and not just screwed into the sheetrock. Normally, these vertical "studs" are on 16" centers and can easily be found by shining a flashlight close to the sheetrock wall and looking for the small blemishes where the screws were installed. Testing to see if they are in the correct spot is very important, and a good technique is to hammer a small nail into the wall until you hit wood. If there is nothing solid after nailing in approximately 1/2", then move 1/2" or so to one side and try again. Keep moving until you are sure that you know where the wood stud is located.



These small holes will be covered by your BULLRACK when its installed, so the cosmetics are not so much an issue. Having the BULLRACK solidly attached is the issue!

You can use a Phillips screwdriver, but your life will be made easier if you have an electric drill/screwdriver.

Make sure that the plastic washer is installed on the 2 1/2" x #10 screw (this will lessen the chance that the decal will be damaged if you over-tighten the screw). **TIP:** rub the screw threads with a bar of soap and they will go into the wood much more easily.



Install the upper screw first but do not tighten completely. Place a carpenters level across the top of the BULLRACK and level it. Install the second screw/washer and tighten both screws snugly, verifying again that the BULLRACK is level. Test the installation for strength by pulling on the unit. This will ensure that you have not just caught the edge of the wood stud, but that you have gotten a good and solid attachment. If you are mounting pannier mounts then

repeat the same installation for the second BULLRACK. Only you can ensure that the BULLRACK is attached correctly!

Hang your panniers or top case, lock them on their BULLRACKS just as you would on your bike, and feel that sense of security and relief knowing that they are SAFE and off the floor!



Metal Installation:

Almost the same installation as for wood, but use shorter self-tapping screws (perhaps about 1" long) if you are attaching into metal and be sure to get completely into the metal stud in the wall and not just the thin sheet. Be sure to use the plastic washer to protect the decal and finish. Remember: Only YOU can decide if your BULLRACK is safely attached to the wall.

Concrete Block or Poured Concrete Wall:

Lowe's and The Home Depot sell a product called a TAPCON kit that has the correct bit and masonry screws for anchoring into brick, block, or masonry. There may be a more suitable product for your installation. Only YOU can decide if your BULLRACK is safely attached to the wall.

Warranty:

Our warranty covers your BULLRACK Pannier Mount(s) for (1) year from the date of purchase against structural failure and we will guarantee the powder-coated finish to hold up for (1) year from date of purchase. You must ship it back to us at your expense with your "proof of purchase" (original or a copy of your invoice, credit card slip, etc.) and we will send you a new one with a new (1) year warranty. We will cover shipping the new BULLRACK to you. Return to :

BULLRACK
708 Long Laurel Ridge Drive
Lakemont, GA. USA
support@bullrack.com



Thank you for buying American made products..

